

CS650DT

6.5" 2-Way, In-Ceiling, Coaxial, Infinite Baffle, Dual Input Stereo, Single Loudspeaker

The easy to install CS650DT is a full-range stereo ceiling loudspeaker in one single speaker package. It incorporates a dual voice coil MetaPlex woofer with a butyl rubber surround and two silk dome Ferrofluid cooled tweeters. It is the perfect application for bathrooms, hallways and small areas where aesthetics and high fidelity sound are vital and a pair of speakers is not practical.

This revolutionary combination provides superior and more natural sound for both foreground and background applications. The Infinite Baffle design makes it the ideal choice for typical applications in open beam attic or enclosed ceilings.

For efficiency and consistency the CS650DT is timbre matched to the CS650, FIT650, and WS650 series of speakers.

The speaker color is white, and is a close match to Frazee White Shadow 181. It can be painted to match any decor. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations. The perforated powdered coated aluminum alloy grill is long-lasting, corrosion resistant and rust-free.

Four built-in expanding transverse dog leg clamps permit installation with or without pre-wire construction brackets in drywall or material with thickness of 5/16" to 1 3/16".

Electrical connection, up to 12 gauge wire, is made by four gold plated constant tension spring loaded terminals, one pair for Left and one pair for Right signal inputs.

This speaker is also available in a quick connect small bezel edge FastLoc Grill.

With our limited Lifetime warranty you are assured years of superior trouble-free operation.

Part Number	92022
Manual URL	www.currentaudio.com
Accessories	- NC6CB New Construction Bracket - Volume Control



CURRENTAUDIO™



SPECIFICATIONS

Driver	6.5" MetaPlex Composite Cone, Dual Voice Coil with Butyl Rubber Surround
Tweeter Dome Material	Dual .75" (19mm) Silk Ferrofluid Cooled Domes
Crossover	Dual inputs (left and right channel) gold press terminals
Grill specification	Perforated aluminum with scrim cloth
Frequency Response	45Hz - 19kHz
Impedance (nominal)	8 ohms
Power Handling	5 - 75 Watts
SPL	90 dB 1W/1m
Diameter x Depth	9" (229mm) x 3 1/16" (78mm)
Retrofit Cutout Diameter	7 7/8" (200mm)
Standard Single Pack Dimensions (weight)	4 3/8" x 10 3/4" x 11 1/2" (4 lbs)
Master Pack Dimensions 4 each (weight)	17 1/2" x 10 3/4" x 11 1/2" (15 lbs)

