

FIT650

6.5" 2-Way, In-Ceiling, Coaxial, Infinite Baffle Loudspeaker

The easy to install FIT650 is a full-range ceiling loudspeaker with Focused Image Technology™. It incorporates a lightweight Injection Molded Carbon Fiber woofer with a butyl rubber surround and the diffractionless aluminum dome pivoting Ferrofluid cooled tweeter. This Patent Pending pivoting tweeter allows for deeper penetration into the room and a concentrated sound to the sweet spot. This revolutionary combination provides superior and more natural sound for both foreground and background applications.

The FIT series speakers additionally incorporate the unique Patent Pending Three Dimensional Positioning (3-DP) woofer. This design allows the user to separately adjust the angle, tilt and rotation of the woofer so you can direct the sound where you want it, not where you install it.

The Positive Position Lock system (PPL) uses two screws on either side of the woofer that pull the back plane tight and locks the position in place.

In addition, the FIT650 contains a 3 position equalization switch, one each for bass and treble to fine-tune the acoustics and allow for various room surfaces. The Infinite Baffle design makes it the ideal choice for typical applications in open beam attic or enclosed ceilings.

For efficiency and consistency the FIT650 is timbre matched to the CS650 and WS650 series of speakers.

The speaker color is white, and is a close match to Frazee White Shadow 181. It can be painted to match any décor. The speaker enclosure is a durable UV-resistant material that allows for both indoor and outdoor installations. The perforated powder-coated aluminum alloy grill is long lasting, corrosion resistant and rust-free.

Four built-in expanding transverse dogleg clamps permit installation with or without pre-wire construction brackets in drywall or material with thickness of 7/32" to 1 3/16".

Electrical connection, up to 12 gauge wire, is made by gold plated constant tension spring-loaded terminals.

This speaker is also available in a quick connect small bezel edge FastLoc Grill.

With our limited Lifetime warranty you are assured years of superior trouble free operation.

Part Number	92063
Manual URL	www.currentaudio.com
Accessories	- NC6CB New Construction Bracket - Volume Control



CURRENTAUDIO™



SPECIFICATIONS

Driver	6.5" MetaPlex Composite Cone w/Butyl Rubber Surround
Tweeter	Patent Pending Pivoting, Diffraction-less 1" (25mm) Silk Ferrofluid Cooled Dome
Crossover	Gold press terminals
Grill specification	Perforated aluminum with scrim cloth
Frequency Response	42Hz - 20kHz
Impedance (nominal)	8 ohms
Power Handling	5 - 100 Watts
SPL	90 dB 1W/1m
Diameter x Depth	9 5/8" (284mm) x 3 11/16" (94mm)
Retrofit Cutout Diameter	8 5/32" (207mm)
Standard Pair Pack Dimensions (weight)	11" x 13" x 12" (10 lbs)
Master Pack Dimensions 2 pair (weight)	22" x 13" x 12" (20 lbs)



www.currentaudio.com

©2010 Current Audio LLC • 1830 John Towers Avenue, El Cajon, CA 92020 • Sales 866-927-7181

All product specifications are subject to change without notice.

Rev. SS-FIT650 02/10